

LOW TORQUE PLUG VALVE

Low Torque Plug Valves are built to meet and exceed the industry's most stringent requirements in high pressure and erosive service conditions. They are constructed of high strength forged alloy steel bodies and abrasion resistant plug inserts. This ensures not only reliability, but also durability



• Application:

- To isolate flow from either direction, and can provide dependable service for applications such as cementing, fracturing, acidizing, coiled tubing and sand control
- Working Pressure: from 2000 PSI to 15,000 PSI
- Nominal Pipe Size: 1", 1-1/2", 2", 3"
- End Connection: threaded, FIG 1002, Fig 1502
- Sour gas service is available

Valve Size	Working Pressure (PSI)	Operating Torque (ft-lbs)		
		5,000 psi	10,000 psi	15,000 psi
1" x 2"	15,000	75	170	220
2" x 2"	15,000	330	450	510
3" x 3"	15,000	1,050	1,350	2,050

Office Address: -
3rd Floor, Shree Towers, Gawali Dev Road, Bhosari MIDC,
Pune-411026

Contact: +91 93199-98853

Email : abhishekf_eng-ind@do-yamamoto.com /
nikhil_eng-ind@do-yamamoto.com / paul_eng-ind@do-yamamoto.com
Website :www.do-yamamoto.com