

Sea Water Hose



- **Application:** Special designed rubber suction hose for sea water installations mainly on jack up vessels using reels systems.
 - Tube and cover made from high grade rubber with excellent resistance to seawater, weathering and UV radiation.
 - Specially angled high tensile Cord ensure minimum dimensional change under Vacuum and end loads.
 - galvanized steel spiral embedded in breakers excellent crush resistance/recovery-Extra thick corrugated cover prevents spiral push thru when reeled or under load.
 - Max. production lengths 60m delivered on steel reels, shorter lengths coiled.
 - End load calculations available.
 - All hoses electrically discontinuous.
 - Reel systems available upon request.
- **Temperature range:** -30°C to +100°C

 Internal Diameter (inch) (mm)		 Working Pressure (bar) (psi)		 Burst Pressure (bar) (psi)		S Safety Coefficient	 MBR (mm)	 Length Max (mtr.)	 Negative Pressure (Kpa)
4	101.6	20	300	80	1200	4	550	60	-90
5	127	20	300	80	1200	4	650	60	-90
6	152.4	20	300	80	1200	4	800	60	-90

Office Address: -
3rd Floor, Shree Towers, Gawali Dev Road, Bhosari MIDC,
Pune-411026

Contact: +91 93199-98853

Email : abhishekf_eng-ind@do-yamamoto.com /
nikhil_eng-ind@do-yamamoto.com / paul_eng-ind@do-yamamoto.com
Website :www.do-yamamoto.com