

Suction & Delivery Drill Water Hose



Application: Hose for suction and discharge of water and non-corrosive liquids. The robust construction enables the hose to withstand its weight without flattening. They are typically used in sites and daylights to spray water.

Temperature: From -40°F to +212°F.

Construction:

Tube: White, smooth, synthetic rubber.

Reinforcement: High strength synthetic cord, and helix wire.

Cover: Blue, Smooth, synthetic rubber, weathering and ozone resistant.

Branding: continuous white/red stripe "Roughneck Offshore -PL DRILL WATER SD 20-ELECTRICALLY DISCONTINUOUS. Embossed marking "Roughneck -PL DRILL WATER SD 20, I.D-, W.P-, TEMP".

Inside diameter		Outside diameter		Working pressure		Burst pressure		Approx. Weight nominal		Bending radius		Vacuum	Length max	
														
mm	inch	mm	inch	bar	psi	bar	psi	kg/m	lbs/ft	mm	inch	bar	m	ft
51	2	70	2.76	20	300	80	1200	2.59	1.74	280	11.0	0.9	60	200
76	3	95.5	3.76	20	300	80	1200	4.05	2.72	400	15.8	0.9	60	200
102	4	12	4.93	20	300	80	1200	6.78	4.55	550	21.7	0.9	60	200

Office Address: -

3rd Floor, Shree Towers, Gawali Dev Road, Bhosari MIDC,
Pune-411026

Contact: +91 93199-98853

Email : abhishekf_eng-ind@do-yamamoto.com /

nikhil_eng-ind@do-yamamoto.com / paul_eng-ind@do-yamamoto.com

Website :www.do-yamamoto.com